

c) Amendments to the Claims

Kindly cancel claims 6-10 without prejudice or disclaimer of subject matter.


Please amend claims 1-5, 11-15 and 21-30 and add new claims 31-35 as follows. A detailed listing of all the claims that are or were in the application is provided hereafter.

1. (Currently Amended) An electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least one ~~one or two or more~~ kind(s) of charge-transporting material ~~material(s)~~;

wherein at least one ~~kind~~ of said charge-transporting material contained in said photosensitive layer is a charge transporting material having a structure represented by the following Formula (1) and having a molecular weight of from 1,500 to 4,000; and

the charge-transporting material having a structure represented by the following Formula (1) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of from 90% by weight to 100% by weight based on the total weight of the charge transporting material (s) contained in said photosensitive layer:




wherein Ar₁₀₁ to Ar₁₀₈ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent aromatic heterocyclic group, and Z₁₁ to Z₁₅ each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group, and wherein one of Z₁₁ to Z₁₅ in Formula (1) is a substituted or unsubstituted dibenzothiophenylene, and the balance are each a substituted or unsubstituted biphenylene group.

2. (Currently Amended) An electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least one ~~or two or more kind(s)~~ of charge-transporting material ~~material(s)~~;

wherein at least one ~~kind~~ of said charge-transporting material contained in said photosensitive layer is a charge-transporting material having a structure represented by the following Formula (2) and having a molecular weight of from 1,500 to 4,000; and


the charge-transporting material having a structure represented by the following Formula (2) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of from 90% by weight to 100% by weight based on the total weight of the charge-transporting material(s) contained in said photosensitive layer:



wherein Ar₂₀₁ to Ar₂₀₉ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent aromatic heterocyclic group, and Z₂₁ to Z₂₆ each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group, and wherein one of Z₂₁ to Z₂₆ in Formula (2) is a substituted or unsubstituted dibenzofuranylene group or a substituted or unsubstituted dibenzothiophenylylene group, and the balance are each a substituted or unsubstituted biphenylene group.

3. (Currently Amended) An electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;
 - said photosensitive layer contains at least one ~~or two or more kind(s)~~ of charge-transporting material ~~material(s)~~;
 - wherein at least one ~~kind~~ of said charge-transporting material contained in said photosensitive layer is a charge-transporting material having a structure represented by the following Formula (3) and having a molecular weight of from 1,500 to 4,000; and
 - the charge-transporting material having a structure represented by the following Formula (3) and having a molecular weight of from 1,500 to 4,000 is held in

a proportion of from 90% by weight to 100% by weight based on the total weight of the charge-transporting material(s) contained in said photosensitive layer:




wherein Ar₃₀₁ to Ar₃₁₀ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent aromatic heterocyclic group, and Z₃₁ to Z₃₇ each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group, and wherein one of Z₃₁ to Z₃₇ in Formula (3) is a substituted or unsubstituted dibenzofuranylene group or a substituted or unsubstituted dibenzothiophenylylene group, and the balance are each a substituted or unsubstituted biphenylene group.

4. (Currently Amended) An electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least one ~~or two or more kind(s)~~ of charge-transporting material ~~material(s)~~;

wherein at least one kind of said charge-transporting material contained in said photosensitive layer is a charge-transporting material having a structure represented by the following Formula (4) and having a molecular weight of from 1,500 to 4,000; and

the charge-transporting material having a structure represented by the following Formula (4) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of from 90% by weight to 100% by weight based on the total weight of the charge-transporting material(s) contained in said photosensitive layer:



wherein Ar₄₀₁ to Ar₄₁₁ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent aromatic heterocyclic group, and Z₄₁ to Z₄₈ each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group, and wherein one of Z₄₁ to Z₄₈ in Formula (4) is a substituted or unsubstituted dibenzofuranylene group or a substituted or unsubstituted dibenzothiophenylylene group, and the balance are each a substituted or unsubstituted biphenylene group.


5. (Currently Amended) An electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least one ~~or two or more kind(s)~~ of charge-transporting material ~~material(s)~~;

wherein at least one ~~kind~~ of said charge-transporting material contained in said photosensitive layer is a charge-transporting material having a structure

represented by the following Formula (5) and having a molecular weight of from 1,500 to 4,000; and

the charge-transporting material having a structure represented by the following Formula (5) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of from 90% by weight to 100% by weight based on the total weight of the charge-transporting material(s) contained in said photosensitive layer:



wherein Ar₅₀₁ to Ar₅₁₂ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent aromatic heterocyclic group, and Z₅₁ to Z₅₉ each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group, and wherein one of Z₅₁ to Z₅₉ in Formula (5), one is a substituted or unsubstituted dibenzofuranylene group or a substituted or unsubstituted dibenzothiophenylylene group, and the balance are each a substituted or unsubstituted biphenylene group.

Claims 6-10 (Cancelled).

11. (Currently Amended) The electrophotographic photosensitive member according to claim 1, wherein said charge-transporting material having the structure represented by Formula (1) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of 100% by weight based on the total weight of the charge-transporting material(s) contained in said photosensitive layer.

12. (Currently Amended) The electrophotographic photosensitive member according to claim 2, wherein said charge-transporting material having the structure represented by Formula (2) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of 100% by weight based on the total weight of the charge-transporting material(s) contained in said photosensitive layer.

13. (Currently Amended) The electrophotographic photosensitive member according to claim 3, wherein said charge-transporting material having the structure represented by Formula (3) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of 100% by weight based on the total weight of the charge-transporting material(s) contained in said photosensitive layer.

14. (Currently Amended) The electrophotographic photosensitive member according to claim 4, wherein said charge-transporting material having the structure represented by Formula (4) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of 100% by weight based on the total weight of the charge-transporting material(s) contained in said photosensitive layer.

15. (Currently Amended) The electrophotographic photosensitive member according to claim 5, wherein said charge-transporting material having the structure represented by Formula (5) and having a molecular weight of from 1,500 to 4,000

is held in a proportion of 100% by weight based on the total weight of the charge-transporting material(s) contained in said photosensitive layer.

16. (Original) The electrophotographic photosensitive member according to claim 1, wherein said charge-transporting material having the structure represented by Formula (1) and having a molecular weight of from 1,500 to 4,000 is synthesized by successive synthesis.

17. (Original) The electrophotographic photosensitive member according to claim 2, wherein said charge-transporting material having the structure represented by Formula (2) and having a molecular weight of from 1,500 to 4,000 is synthesized by successive synthesis.

18. (Original) The electrophotographic photosensitive member according to claim 3, wherein said charge-transporting material having the structure represented by Formula (3) and having a molecular weight of from 1,500 to 4,000 is synthesized by successive synthesis.

19. (Original) The electrophotographic photosensitive member according to claim 4, wherein said charge-transporting material having the structure represented by Formula (4) and having a molecular weight of from 1,500 to 4,000 is synthesized by successive synthesis.


20. (Original) The electrophotographic photosensitive member according to claim 5, wherein said charge-transporting material having the structure represented by Formula (5) and having a molecular weight of from 1,500 to 4,000 is synthesized by successive synthesis.

21. (Currently Amended) A process cartridge comprising an electrophotographic photosensitive member and at least one means selected from the group consisting of a charging means, a developing means and a cleaning means which are integrally supported; and being detachably mountable on the main body of an electrophotographic apparatus; the electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least one ~~or two or more kind(s)~~ of charge-transporting material ~~material(s)~~;

wherein at least one ~~kind~~ of said charge-transporting material contained in said photosensitive layer is a charge-transporting material having a structure represented by the following Formula (1) and having a molecular weight of from 1,500 to 4,000; and

the charge-transporting material having a structure represented by the following Formula (1) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of from 90% by weight to 100% by weight based on the total weight of the charge-transporting material~~(s)~~ contained in said photosensitive layer:




wherein Ar₁₀₁ to Ar₁₀₈ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent aromatic heterocyclic group, and Z₁₁ to Z₁₅ each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group, and wherein one of Z₁₁ to Z₁₅ in Formula (1) is a substituted or unsubstituted dibenzothiophenylene, and the balance are each a substituted or unsubstituted biphenylene group.

22. (Currently Amended) A process cartridge comprising an electrophotographic photosensitive member and at least one means selected from the group consisting of a charging means, a developing means and a cleaning means which are integrally supported; and being detachably mountable on the main body of an electrophotographic apparatus; the electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least ~~one or two or more kind(s)~~ of charge-transporting material ~~material(s)~~;

wherein at least one ~~kind~~ of said charge-transporting material contained in said photosensitive layer is a charge-transporting material having a structure represented by the following Formula (2) and having a molecular weight of from 1,500 to 4,000; and

the charge-transporting material having a structure represented by the following Formula (2) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of from 90% by weight to 100% by weight based on the total weight of the charge-transporting material(s) contained in said photosensitive layer:




wherein Ar₂₀₁ to Ar₂₀₉ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent aromatic heterocyclic group, and Z₂₁ to Z₂₆ each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group, and wherein one of Z₂₁ to Z₂₆ in Formula (2) is a substituted or unsubstituted dibenzofuranylene group or a substituted or unsubstituted dibenzothiophenylylene group, and the balance are each a substituted or unsubstituted biphenylene group.

23. (Currently Amended) A process cartridge comprising an electrophotographic photosensitive member and at least one means selected from the group consisting of a charging means, a developing means and a cleaning means which are integrally supported; and being detachably mountable on the main body of an electrophotographic apparatus; the electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least ~~one or two or more kind(s)~~
of charge-transporting material ~~material(s)~~;

wherein at least one ~~kind~~ of said charge-transporting material
contained in said photosensitive layer is a charge-transporting material having a structure
represented by the following Formula (3) and having a molecular weight of from 1,500 to
4,000; and

the charge-transporting material having a structure represented by
the following Formula (3) and having a molecular weight of from 1,500 to 4,000 is held in
a proportion of from 90% by weight to 100% by weight based on the total weight of the
charge-transporting material(~~s~~) contained in said photosensitive layer:



wherein Ar₃₀₁ to Ar₃₁₀ each independently represent a substituted or unsubstituted
monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent
aromatic heterocyclic group, and Z₃₁ to Z₃₇ each independently represent a substituted or
unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent
aromatic heterocyclic group, and wherein one of Z₃₁ to Z₃₇ in Formula (3) is a substituted or
unsubstituted dibenzofuranylene group or a substituted or unsubstituted
dibenzothiophenylylene group, and the balance are each a substituted or unsubstituted
biphenylene group.


24. (Currently Amended) A process cartridge comprising an
electrophotographic photosensitive member and at least one means selected from the group

consisting of a charging means, a developing means and a cleaning means which are integrally supported; and being detachably mountable on the main body of an electrophotographic apparatus; the electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least one ~~or two or more kind(s)~~ of charge-transporting material ~~material(s)~~;

wherein at least one ~~kind~~ of said charge-transporting material contained in said photosensitive layer is a charge-transporting material having a structure represented by the following Formula (4) and having a molecular weight of from 1,500 to 4,000; and

the charge-transporting material having a structure represented by the following Formula (4) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of from 90% by weight to 100% by weight based on the total weight of the charge-transporting material(s) contained in said photosensitive layer:



wherein Ar₄₀₁ to Ar₄₁₁ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent aromatic heterocyclic group, and Z₄₁ to Z₄₈ each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group, and wherein one of Z₄₁ to Z₄₈ in Formula (4) is a substituted or unsubstituted dibenzofuranylene group or a substituted or unsubstituted


dibenzothiophenylene group, and the balance are each a substituted or unsubstituted biphenylene group.

25. (Currently Amended) A process cartridge comprising an electrophotographic photosensitive member and at least one means selected from the group consisting of a charging means, a developing means and a cleaning means which are integrally supported; and being detachably mountable on the main body of an electrophotographic apparatus; the electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least ~~one or two or more kind(s)~~ of charge-transporting material ~~material(s)~~;

wherein at least one ~~kind~~ of said charge-transporting material contained in said photosensitive layer is a charge-transporting material having a structure represented by the following Formula (5) and having a molecular weight of from 1,500 to 4,000; and

the charge-transporting material having a structure represented by the following Formula (5) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of from 90% by weight to 100% by weight based on the total weight of the charge-transporting material(s) contained in said photosensitive layer:



wherein Ar₅₀₁ to Ar₅₁₂ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent


aromatic heterocyclic group, and Z_{51} to Z_{59} each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group, and wherein one of Z_{51} to Z_{59} in Formula (5), one is a substituted or unsubstituted dibenzofuranylene group or a substituted or unsubstituted dibenzothiophenylene group, and the balance are each a substituted or unsubstituted biphenylene group.

26. (Currently Amended) An electrophotographic apparatus comprising an electrophotographic photosensitive member, a charging means, an exposure means, a developing means and a transfer means; the electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least ~~one or two or more kind(s)~~ of charge-transporting material ~~material(s)~~;

wherein at least one ~~kind~~ of said charge-transporting material contained in said photosensitive layer is a charge-transporting material having a structure represented by the following Formula (1) and having a molecular weight of from 1,500 to 4,000; and

the charge-transporting material having a structure represented by the following Formula (1) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of from 90% by weight to 100% by weight based on the total weight of the charge-transporting material(s) contained in said photosensitive layer:




wherein Ar₁₀₁ to Ar₁₀₈ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent aromatic heterocyclic group, and Z₁₁ to Z₁₅ each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group, and wherein one of Z₁₁ to Z₁₅ in Formula (1) is a substituted or unsubstituted dibenzothiophenylene, and the balance are each a substituted or unsubstituted biphenylene group.

27. (Currently Amended) An electrophotographic apparatus comprising an electrophotographic photosensitive member, a charging means, an exposure means, a developing means and a transfer means; the electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least one ~~or two or more kind(s)~~ of charge-transporting material ~~material(s)~~;

wherein at least one ~~kind~~ of said charge-transporting material contained in said photosensitive layer is a charge-transporting material having a structure represented by the following Formula (2) and having a molecular weight of from 1,500 to 4,000; and

the charge-transporting material having a structure represented by the following Formula (2) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of from 90% by weight to 100% by weight based on the total weight of the charge-transporting material(s) contained in said photosensitive layer:




wherein Ar₂₀₁ to Ar₂₀₉ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent aromatic heterocyclic group, and Z₂₁ to Z₂₆ each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group, and wherein one of Z₂₁ to Z₂₆ in Formula (2) is a substituted or unsubstituted dibenzofuranylene group or a substituted or unsubstituted dibenzothiophenylylene group, and the balance are each a substituted or unsubstituted biphenylene group.

28. (Currently Amended) An electrophotographic apparatus comprising an electrophotographic photosensitive member, a charging means, an exposure means, a developing means and a transfer means; the electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least ~~one or two or more kind(s)~~ of charge-transporting material ~~material(s)~~;

wherein at least one kind of said charge-transporting material contained in said photosensitive layer is a charge-transporting material having a structure represented by the following Formula (3) and having a molecular weight of from 1,500 to 4,000; and

the charge-transporting material having a structure represented by the following Formula (3) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of from 90% by weight to 100% by weight based on the total weight of the charge-transporting material(s) contained in said photosensitive layer:



wherein Ar₃₀₁ to Ar₃₁₀ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent aromatic heterocyclic group, and Z₃₁ to Z₃₇ each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group, and wherein one of Z₃₁ to Z₃₇ in Formula (3) is a substituted or unsubstituted dibenzofuranylene group or a substituted or unsubstituted dibenzothiophenylylene group, and the balance are each a substituted or unsubstituted biphenylene group.


29. (Currently Amended) An electrophotographic apparatus comprising an electrophotographic photosensitive member, a charging means, an exposure means, a developing means and a transfer means; the electrophotographic photosensitive member

comprising a conductive support and a photosensitive layer provided on the support,
wherein;

said photosensitive layer contains at least one ~~or two or more kind(s)~~
~~of~~ charge-transporting materials material(s);

wherein at least one ~~kind~~ of said charge-transporting material
contained in said photosensitive layer is a charge-transporting material having a structure
represented by the following Formula (4) and having a molecular weight of from 1,500 to
4,000; and

the charge-transporting material having a structure represented by
the following Formula (4) and having a molecular weight of from 1,500 to 4,000 is held in
a proportion of from 90% by weight to 100% by weight based on the total weight of the
charge-transporting material material(s) contained in said photosensitive layer:




wherein Ar₄₀₁ to Ar₄₁₁ each independently represent a substituted or unsubstituted
monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent
aromatic heterocyclic group, and Z₄₁ to Z₄₈ each independently represent a substituted or
unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent
aromatic heterocyclic group, and wherein one of Z₄₁ to Z₄₈ in Formula (4) is a substituted or
unsubstituted dibenzofuranylene group or a substituted or unsubstituted
dibenzothiophenylylene group, and the balance are each a substituted or unsubstituted
biphenylene group.

30. (Currently Amended) An electrophotographic apparatus comprising an electrophotographic photosensitive member, a charging means, an exposure means, a developing means and a transfer means; the electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least one ~~or two or more kind(s)~~ of charge-transporting material ~~material(s)~~;

wherein at least one kind of said charge-transporting material contained in said photosensitive layer is a charge-transporting material having a structure represented by the following Formula (5) and having a molecular weight of from 1,500 to 4,000; and

the charge-transporting material having a structure represented by the following Formula (5) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of from 90% by weight to 100% by weight based on the total weight of the charge-transporting material ~~material(s)~~ contained in said photosensitive layer:



wherein Ar₅₀₁ to Ar₅₁₂ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent aromatic heterocyclic group, and Z₅₁ to Z₅₉ each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group, and wherein one of Z₅₁ to Z₅₉ in Formula (5), one is a substituted or unsubstituted dibenzofuranylene group or a substituted or unsubstituted


dibenzothiophenylene group, and the balance are each a substituted or unsubstituted biphenylene group.

31. (New) An electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least one charge-transporting material;

wherein at least one of said charge-transporting material contained in said photosensitive layer is a charge-transporting material having a structure represented by the following Formula (1) and having a molecular weight of from 1,500 to 4,000; and

the charge-transporting material having a structure represented by the following Formula (1) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of 100% by weight based on the total weight of the charge-transporting material contained in said photosensitive layer:




wherein Ar₁₀₁ to Ar₁₀₈ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent aromatic heterocyclic group, and Z₁₁ to Z₁₅ each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group.

32. (New) An electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least one charge-transporting material;

wherein at least one of said charge-transporting material contained in said photosensitive layer is a charge-transporting material having a structure represented by the following Formula (2) and having a molecular weight of from 1,500 to 4,000; and

the charge-transporting material having a structure represented by the following Formula (2) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of 100% by weight based on the total weight of the charge-transporting material contained in said photosensitive layer:




wherein Ar₂₀₁ to Ar₂₀₉ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent aromatic heterocyclic group, and Z₂₁ to Z₂₆ each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group.

33. (New) An electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least one charge-transporting material;

wherein at least one of said charge-transporting material contained in said photosensitive layer is a charge-transporting material having a structure represented by the following Formula (3) and having a molecular weight of from 1,500 to 4,000; and

the charge-transporting material having a structure represented by the following Formula (3) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of 100% by weight based on the total weight of the charge-transporting material contained in said photosensitive layer:




wherein Ar₃₀₁ to Ar₃₁₀ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent aromatic heterocyclic group, and Z₃₁ to Z₃₇ each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group.

34. (New) An electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least one charge-transporting material;

wherein at least one of said charge-transporting material contained in said photosensitive layer is a charge-transporting material having a structure represented by the following Formula (4) and having a molecular weight of from 1,500 to 4,000; and the charge-transporting material having a structure represented by the following Formula (4) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of 100% by weight based on the total weight of the charge-transporting material contained in said photosensitive layer:




wherein Ar₄₀₁ to Ar₄₁₁ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent aromatic heterocyclic group, and Z₄₁ to Z₄₈ each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group.

35. (New) An electrophotographic photosensitive member comprising a conductive support and a photosensitive layer provided on the support, wherein;

said photosensitive layer contains at least one charge-transporting material;

wherein at least one of said charge-transporting material contained in said photosensitive layer is a charge-transporting material having a structure represented by the following Formula (5) and having a molecular weight of from 1,500 to 4,000; and

the charge-transporting material having a structure represented by the following Formula (5) and having a molecular weight of from 1,500 to 4,000 is held in a proportion of 100% by weight based on the total weight of the charge-transporting material contained in said photosensitive layer:



wherein Ar₅₀₁ to Ar₅₁₂ each independently represent a substituted or unsubstituted monovalent aromatic carbocyclic group or a substituted or unsubstituted monovalent aromatic heterocyclic group, and Z₅₁ to Z₅₉ each independently represent a substituted or unsubstituted divalent aromatic carbocyclic group or a substituted or unsubstituted divalent aromatic heterocyclic group.